

GENELEC PRICE LIST

08 January 2010

Price NZD excl. GST

Analogue Two-Way Bi-Amplified Active Monitors

6010APM	6010A Compact, Two-way Active Nearfield Monitor - Black Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 76 mm (3") LF and 19 mm (.75") HF drive units. RCA input connector. Integrated crossover and amps - 12W and 12W. Room response controls on rear panel. On-Off and volume control on the back panel. 3/8" mic stand thread. Integrated M6 mounting threads and VESA 75 mm M4 in the back. Wall mount bracket included. Iso-Pod™ table support included. Matt black painted finish. Weight 1,4 kg.	460.00
6010ASM	6010A Compact, Two-way Active Nearfield Monitor - Silver Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 76 mm (3") LF and 19 mm (.75") HF drive units. RCA input connector. Integrated crossover and amps - 12W and 12W. Room response controls on rear panel. On-Off and volume control on the back panel. 3/8" mic stand thread. Integrated M6 mounting threads and VESA 75 mm M4 in the back. Wall mount bracket included. Iso-Pod™ table support included. Silver painted finish. Weight 1,4 kg.	460.00
6010AWM	6010A Compact, Two-way Active Nearfield Monitor - White Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 76 mm (3") LF and 19 mm (.75") HF drive units. RCA input connector. Integrated crossover and amps - 12W and 12W. Room response controls on rear panel. On-Off and volume control on the back panel. 3/8" mic stand thread. Integrated M6 mounting threads and VESA 75 mm M4 in the back. Wall mount bracket included. Iso-Pod™ table support included. White painted finish. Weight 1,4 kg.	460.00
8020BPM	8020B Compact, Two-way Active Nearfield Monitor - Black Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 100 mm (4") LF and 19 mm (.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 20W and 20W. Room response controls on rear panel. On-Off and volume control all in one on the front panel. 3/8" mic stand thread. Integrated M6 mounting threads in the back. Wall mount bracket included. Iso-Pod™ table support included. Matt black painted finish. Weight 3,7 kg	720.00
8020BSM	8020B Compact, Two-way Active Nearfield Monitor - Silver Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 100 mm (4") LF and 19 mm (.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 20W and 20W. Room response controls on rear panel. On-Off and volume control all in one on the front panel. 3/8" mic stand thread. Integrated M6 mounting threads in the back. Wall mount bracket included. Iso-Pod™ table support included. Silver painted finish. Weight 3,7 kg	775.00
8020BWM	8020B Compact, Two-way Active Nearfield Monitor - White Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 100 mm (4") LF and 19 mm (.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 20W and 20W. Room response controls on rear panel. On-Off and volume control all in one on the front panel. 3/8" mic stand thread. Integrated M6 mounting threads in the back. Wall mount bracket included. Iso-Pod™ table support included. White painted finish. Weight 3,7 kg	775.00
8030APM	8030A Compact, Two-way Active Nearfield Monitor - Black Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 130 mm (5") LF and 19 mm (.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 40W and 40W. Room response controls on rear panel. On-Off and volume control on the front panel. 3/8" mic stand thread. Integrated M6 mounting threads in the back. Iso-Pod™ table support included. Matt black painted finish. Weight 5,6 kg.	1,080.00
8030ASM	8030A Compact, Two-way Active Nearfield Monitor - Silver Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 130 mm (5") LF and 19 mm (.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 40W and 40W. Room response controls on rear panel. On-Off and volume control on the front panel. 3/8" mic stand thread. Integrated M6 mounting threads in the back. Iso-Pod™ table support included. Silver painted finish. Weight 5,6 kg.	1,135.00
8030AWM	8030A Compact, Two-way Active Nearfield Monitor - White Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 130 mm (5") LF and 19 mm (.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 40W and 40W. Room response controls on rear panel. On-Off and volume control on the front panel. 3/8" mic stand thread. Integrated M6 mounting threads in the back. Iso-Pod™ table support included. White painted finish. Weight 5,6 kg.	1,135.00
8130APM	8130A Compact, Two-way Digital Input Active Monitor As 8030AP but with AES/EBU Digital input combined with analogue input XLR connector. Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 130 mm (5") LF and 19 mm (.75") HF drive units. Digital or analogue signal through XLR output connector. Integrated crossover and amps - 40W and 40W. Room response controls on rear panel. On-Off and volume control on the front panel. 3/8" mic stand thread. Integrated M6 mounting threads in the back. Iso-Pod™ table support included. Matt black painted finish. Weight 5,6 kg.	1,495.00
8040APM	8040A Two-way Active Nearfield Monitor - Black Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 165 mm (6.5") LF and 19 mm (.75") HF drive units. Balanced XLR connector. Integrated crossover and amps - 90W and 90W. Integrated M6 mounting threads in the back. Room response controls on rear panel. Iso-Pod™ table support included. Matt black painted finish. Weight 8,6 kg.	1,720.00

NZ Dollar prices shown are ex-Wellington or Auckland warehouse, exclusive of GST.

All prices are subject to Protel Standard Conditions of Sale and subject to change without notice.

GENELEC PRICE LIST

08 January 2010

Price NZD excl. GST

Analogue Two-Way Bi-Amplified Active Monitors

8040AWM	8040A Two-way Active Nearfield Monitor - White Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 165 mm (6.5") LF and 19 mm (.75") HF drive units. Balanced XLR connector. Integrated crossover and amps - 90W and 90W. Integrated M6 mounting threads in the back. Room response controls on rear panel. Iso-Pod™ table support included. White painted finish. Weight 8,6 kg.	1,820.00
8050APM	8050A Two-way Active Nearfield Monitor - Black Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded 205 mm (8") LF and 25 mm (1") HF drive units. Balanced XLR connector. Integrated crossover and amps - 150W and 120W. Integrated M6 mounting threads in the back. Room response controls on rear panel. Iso-Pod™ table support included. Matt black painted finish. Weight 12,7 kg.	2,690.00
8050AWM	8050A Two-way Active Nearfield Monitor - White Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded 205 mm (8") LF and 25 mm (1") HF drive units. Balanced XLR connector. Integrated crossover and amps - 150W and 120W. Integrated M6 mounting threads in the back. Room response controls on rear panel. Iso-Pod™ table support included. White painted finish. Weight 12,7 kg.	2,840.00

Active Subwoofer Systems

5040APM	5040A Active Subwoofer. Deep drawn steel cabinet with optimized reflex port, design to support up to 5pcs of 6010A. System volume control included. Single 165 mm (6.5") magnetically shielded long throw cone driver to produce up to 98 dB SPL in half space. RCA in and output connectors. 40 W amplifier with very low THD and IM distortion. Weight 6,3 kg.	940.00
5040ASM	5040A Active Subwoofer - Silver As 5040APM above but in silver painted finish	940.00
5040AWM	5040A Active Subwoofer - White As 5040APM above but in white painted finish	940.00
7050BP	7050B Active Subwoofer. Featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and 5.1 channel connection system. Single 205 mm (8") magnetically shielded long throw cone driver to produce up to 100 dB SPL in half space. 70W amplifier with very low THD and IM distortion. Weight 18kg.	1,760.00
7060BP	7060B Active Subwoofer. Featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 6.1 channel Bass Manager. Single 210 mm (10") magnetically shielded long throw cone driver to produce up to 108 dB SPL in half space. 120W amplifier with very low THD and IM distortion. Driver overload protection and power-on signal muting. Sum out to enable coupling of two or more subwoofers. Weight 28kg.	3,230.00
7070AP	7070A Active Subwoofer. Featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 6.1 channel Bass Manager. Single 300 mm (12") magnetically shielded long throw cone driver to produce up to 112 dB SPL in half space. 250W amplifier with very low THD and IM distortion. Driver overload protection and power-on signal muting. Sum out to enable coupling of two or more subwoofers. Weight 50kg.	4,645.00
7071AP	7071A Active Subwoofer. Featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 6.1 channel Bass Manager. Dual 300 mm (12") magnetically shielded long throw cone drivers to produce up to 118 dB SPL in half space. 500W amplifier with very low THD and IM distortion. Driver overload protection and power-on signal muting. Sum out to enable coupling of two or more subwoofers. Weight 81kg.	6,955.00
7073AP	7073A Active Subwoofer. LF extension down to 19 Hz. Flexible 6.1 channel Bass Manager. Four 300 mm (12") magnetically shielded long throw cone drivers to produce up to 124 dB SPL in half space. 1000W amplifier with very low THD and IM distortion. Driver and amplifier overload protection and power-on signal muting. Sum out to enable coupling of two or more subwoofers. Weight 120kg.	11,080.00

DSP Active Monitors

8240APM	8240A DSP Two-way Monitor System. Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ and magnetically shielded 165 mm (6.5") LF and 19 mm (3/4") HF drive units. Integrated crossover and amplifiers – 90 W and 90 W. Balanced 165 mm (6.5") LF and 19 mm (3/4") HF drive units. Integrated crossover and amplifiers – 90 W and 90 W. Balanced analog XLR input connector and digital AES/EBU In and Thru XLR connectors. Dual Genelec Loudspeaker Manager™ (GLM™). Control Network connectors. Controls for Stand-Alone operational mode on rear panels. Integrated rear M6 mounting threads. Iso-Pod™ table support included. Matt black painted finish. Weight 9,4 kg.	2,190.00
8250APM	8250A DSP Two-way Monitor System. Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ and magnetically shielded 205 mm (8") LF and 25 mm (1") HF drive units. Integrated crossover and amplifiers – 150 W and 120 W. Balanced analog XLR input connector and digital AES/EBU In and Thru XLR connectors. Dual Genelec Loudspeaker Manager™ (GLM™). Control Network connectors. Controls for Stand-Alone operational mode on rear panels. Integrated rear M6 mounting threads. Iso-Pod™ table support included. Matt black painted finish. Weight 14,6 kg.	3,110.00
8260APM	8260A DSP Three-way Monitor System. The new Genelec 8260A 3-way DSP system is a masterpiece in electro-acoustic design which features major advances in audio driver technology integrated to a sophisticated enclosure design. Genelec MDC™ Minimum Diffraction Coaxial Mid/High driver technology takes a	6,530.00

NZ Dollar prices shown are ex-Wellington or Auckland warehouse, exclusive of GST.

All prices are subject to Protel Standard Conditions of Sale and subject to change without notice.

GENELEC PRICE LIST

08 January 2010

Price NZD excl. GST

DSP Active Monitors

big step in perfecting audio quality in professional active studio monitors. This breakthrough in coaxial driver design provides more accurate imaging and improved sound quality both on the acoustical axis as well as off-axis. The extremely smooth frequency response leads to outstanding clarity and definition of the inner details of the music. The 8260A combines, for the first time, a coaxial driver (MDC™) with a modern waveguide technology (DCW™), ensuring drivers to couple coherently over their full operating bandwidth, as well as creating coincident mid-frequency/high frequency point source. Bass-10" Midrange-5" laminate cone Treble 3/4" coaxial Al-dome, Crossover frequencies 490 Hz, 3 kHz Free field frequency response 29 Hz - 21 kHz (± 1 dB) Amplifier power /ch Bass 150 W Midrange 120 W Treble 120 W
Speaker dimensions (H x W x D) mm 570 x 358 x 344 mm (Height with Iso-Pod™ 593 mm) Speaker weight 27.5 kg (60.5 lb)

Active DSP Subwoofer Systems

7261AP	SE7261A DSP Active Subwoofer. Featuring the Genelec Lamina Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Single 210 mm (10") magnetically shielded long throw cone driver with 120 W amplifier to produce up to 108 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM.SE™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration. GLM.SE™ software with SE7261A subwoofer can control up to 8 pcs of 8130A loudspeakers. Weight 27 kg.	3,965.00
7260AP	7260A DSP Active Subwoofer. Featuring the Genelec Lamina Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Single 210 mm (10") magnetically shielded long throw cone driver with 120W amplifier to produce up to 108 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration. Weight 27kg.	3,965.00
7270AP	7270A Active Subwoofer. Featuring the Genelec Lamina Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Single 300 mm (12") magnetically shielded long throw cone driver with 250W amplifier to produce up to 112 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration. Weight 51kg.	5,260.00
7271AP	7271A Active Subwoofer. Featuring the Genelec Lamina Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Dual 300 mm (12") magnetically shielded long throw cone driver with 500W amplifier to produce up to 118 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration. Weight 82kg.	8,190.00

GLM Packages & Accessories

8200-401	GLM Genelec Loudspeaker Manager Package GLM™ Genelec Loudspeaker Manager package featuring AutoCal™ includes; software CD (PC & Mac), GLM System Operating Manual, Quick Connection Guide, GLM™ Network Interface with built-in microphone amplifier, USB cable, Network cable, Genelec 8200A Calibration microphone and holder, 3.5mm jack-jack Measurement Signal cable and cable labels. GLM™ software is available for Windows XP and Mac OS X, both Power PC and Intel based platforms operating systems.	1,180.00
8200-402	GLM Multiroom Expansion Package GLM™ Multiroom Expansion package includes; GLM™ Network Interface with built-in microphone amplifier, USB cable, Network cable and Cable labels. This package is useful for multiroom facilities as it saves purchasing multiple microphones and other parts. (No microphone or Software included)	530.00
8200-501	GLM.SE Genelec Loudspeaker Manager Package GLM.SE™ Genelec Loudspeaker Manager package for SE7261A featuring AutoCal™ includes; software CD, GLM.SE System Operating Manual, Quick Connection Guide, GLM™ Network Interface with built-in microphone amplifier, USB cable, Network cable, Genelec 8200A Calibration microphone and holder, 3.5mm jack-jack Measurement Signal cable and cable labels. GLM.SE™ software is available for Windows XP and Mac.	965.00
8200-502	GLM.SE Multiroom Expansion Package GLM.SE™ Multiroom Expansion package includes; GLM™ Network Interface with built-in microphone amplifier, USB cable, Network cable and Cable labels. This package is useful for multiroom facilities as it saves purchasing multiple microphones and other parts. (No microphone or Software included)	530.00
AD9200A	AD9200A A/D Converter 8-channel A to D converter providing analogue inputs into 4 AES/EBU outputs for the 7200-series DSP subwoofers. 1U high, 19", including one 8ch balanced analogue inputs on DB 25 pin connector with M2,5 metric threads (Tascam standard) 192 kHz / 24Bit internal sample rate converter. Separate 12 volt power supply is included.	1,500.00
8000-910	Griffin volume control PowerMate aluminium, USB volume control, software for Windows and Mac included.	280.00

NZ Dollar prices shown are ex-Wellington or Auckland warehouse, exclusive of GST.

All prices are subject to Protel Standard Conditions of Sale and subject to change without notice.

GENELEC PRICE LIST

08 January 2010

Price NZD excl. GST

Active Signal Balancer

DI8A	DI8A Active Balancer. 8-Channel Active Balancer to convert an unbalanced line signal (RCA) to a balanced line signal (XLR). +6dB switch to raise signal level. One channel with duplicated outputs.	1,605.00
------	--	----------

Home Theatre / Custom Install

6020APM	6020A Compact Two-Way Active Loudspeaker - Black Die cast aluminium cabinet, magnetically shielded with 105 mm (4") LF and 19 mm (3/4") HF drive units and Directivity Control Waveguide™ (DCW™). Integrated active electronic crossover, overload protection circuitry and two 20 W amplifiers, XLR balanced and RCA unbalanced connectors. Room response controls on rear panel. Easy to install with integrated wall mount attach points and 3/8" mic stand thread. Durable black painted finish.	850.00
6020ASM	6020A Compact Two-Way Active Loudspeaker - Silver As 6020APM above but in silver metallic finish...	955.00
6020AWM	6020A Compact Two-Way Active Loudspeaker - White As 6020APM above but in white finish...	955.00
6040ASM	6040A Design Floor-standing Loudspeaker Die cast aluminium cabinet, magnetically shielded with 210mm (8") LF and 25mm (1") HF drive units and Directivity Control Waveguide™ (DCW™). Floor stand include integrated active electronic crossover, overload protection circuitry, room response controls and two 120 W amplifiers. Design by Harri Koskinen. XLR balanced and RCA unbalanced connectors. Speaker and floor stand in silver metallic finish. Autostart capable with a connector strip for 12 V trigger and contact closure. Signal sensing auto-On/Off circuit.	4,335.00
5050APM	5050A Active Subwoofer System With single 200 mm (8") active driver and dual 200 mm (8") passive radiators. Amplifier 70 W, sub-link feature, XLR balanced and RCA unbalanced LFE input connectors and three pairs of bass-managed RCA In/Out connectors. Level and phase controls. Signal sensing auto-On/Off circuit. Durable black painted finish. Network cable and Cable labels. This package is useful for multiroom facilities as it saves purchasing multiple microphones and other parts. (No microphone or Software included)	2,310.00

Three-Way Tri-Amplified Active Monitors

1037CE	1037C Three-way Active Monitor. Magnetically shielded 300 mm (12") LF, GENELEC 130 mm (5") MF and 25 mm (1") HF drive units. Integrated crossovers and amps, 180W, 120W and 120W. Room response controls on rear panel. Black veneer finish. Weight 37 kg. As 1037CE but with durable black painted "Producer" finish Orientation of the DCW, see illustration on page 4.	7,040.00
1038BE	1038B Three-way Active Monitor. Magnetically shielded 380 mm (15") LF, GENELEC 130 mm (5") MF and 25 mm (1") HF drive units. Integrated crossovers and amps, 400W, 120W, and 120W. Room response controls on rear panel. Black veneer finish. Weight 60 kg. As 1038BE but with durable black painted "Producer" finish Orientation of the DCW, see illustration on page 4.	9,935.00
1038BCE-VL	1038BC Centre Channel Three-way Active Monitor. Magnetically shielded Dual 250 mm (10") LF, GENELEC 130 mm (5") MF, 25 mm (1") HF drive units. System includes speaker enclosure in black veneer finish in front and durable black painted "Producer" finish in sides and back, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 400W, 120W and 120W. 10 m cable included. Weight 60 + 14kg. Orientation of the DCW, see illustration on page 4.	11,040.00
1038BCFM	1038CF Three-way Active Monitor. Magnetically shielded, dual 205 mm (8") LF, GENELEC 130 mm (5") MF and 25 mm (1") HF drive units. Integrated crossovers and amps, 180W, 120W and 120W. Room response controls on rear panel. Black painted "Producer" finish. Weight 39 kg.	7,640.00

Main Control Room Active Monitors

1034BE-VU	1034B Three-way Main Control Room Active Monitor. Freight NOT Included. Flush mount design. Magnetically shielded, dual 300 mm (12") LF, GENELEC 130 mm (5") MF, and 25 mm (1") HF drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 2 x 400W, 350W, and 120W per amp module. 10 m cable included as standard. Other lengths available, see page 8. Weight 73 + 30kg.	Call Protel
1034BCE-VL	1034BC Centre Channel Three-way Active Monitor Freight NOT Included. Flush mount design. Magnetically shielded, dual 300 mm (12") LF, GENELEC 130 mm (5") MF, 25 mm (1") HF drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Matches the 1034B Main Control Room Monitor Systems. Amplification 2 x 400W, 350W and 120W. 10 m cable included as standard. Other lengths available, see page 8. Weight 84 + 30kg. Orientation of the DCW, see illustration on page 4.	Call Protel

NZ Dollar prices shown are ex-Wellington or Auckland warehouse, exclusive of GST.

All prices are subject to Protel Standard Conditions of Sale and subject to change without notice.

GENELEC PRICE LIST

08 January 2010

Price NZD excl. GST

Main Control Room Active Monitors

1039AE-VU	1039A Three-way Main Control Room Active Monitor. Freight NOT Included. Flush mount design. Magnetically shielded, dual 380 mm (15") LF, GENELEC 130 mm (5") MF, and 25 mm (1") HF drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 2 x 400W, 350W and 120W per amp module. 10 m cable included as standard. Other lengths available, see page 8. Weight 115 + 30kg. Orientation of the DCW, see illustration below.	Call Protel
1035BE-VU	1035B Three-way Main Control Room Active Monitor . Freight NOT Included. Flush mount design for large control rooms. Dual 380 mm (15") LF, Dual GENELEC 130 mm (5") MF and 25 mm (1") HF compression drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 2 x 1100W, 600W, and 300W (3.1kW) per amp module. 10 m cable included as standard. Other lengths available, see page 8. Weight 142 + 71kg. Orientation of the DCW, see illustration below.	Call Protel
1036AE-VU	1036A Three-way Main Control Room Active Monitor. Freight NOT Included. Flush mount design for large control rooms. Dual 460 mm (18") LF, Dual GENELEC 130 mm (5") MF and 25 mm (1") HF compression drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 2 x 1100W,600W, and 300W (3.1kW) per amp module. 10 m cable included as standard. Other lengths available, see page 8. Weight 182 + 71kg. Orientation of the DCW, see illustration below.	Call Protel

Options for Two-Way Bi-Amplified Active Monitors

Options for 6010A

6010-410B	Wall Mount Bracket, black (included in 6010A)	60.00
6010-410W	Wall Mount Bracket, white (included in 6010A)	60.00
8010-408	Stand Plate for 6010A Iso-Pod (K&M 19621-329-55)	105.00
8010-202B	Wall and Ceiling Mount, black (packed in pairs)	115.00
8010-202S	Wall and Ceiling Mount, silver (packed in pairs)	115.00
8010-202W	Wall and Ceiling Mount, white (packed in pairs)	115.00
6010-421	Soft carrying bag for two monitors	225.00
6010-423	Laptop carrying bag for two monitors	255.00

Options for 8020A

8000-409B	Floor stand (K&M 26741-029-55)	335.00
8000-403	Floor stand (K&M 26000-300-55).	225.00
8000-412B	Wall mount with T-plate, black (K&M 24179-000-55)	200.00
8000-412W	Wall mount with T-plate, white (K&M 24179-000-57)	200.00
8030-404-W	Wall mount, white (Omnimount 20.5 WA)	230.00
8000-402B	Wall bracket, black (K&M 24475-000-55)	290.00
8000-402W	Wall bracket, white (K&M 24475-000-57).	290.00
8000-410B	Wall mount bracket, black (included in 8020A).	30.00
8000-410W	Wall mount bracket, white (included in 8020A).	30.00
8000-406	Table stand (K&M 23310-370-55).	205.00
8020-408	Stand plate for 8020A Iso-Pod (K&M 19622-329-55)	135.00
8000-415B	Ceiling mount, black (K&M 24490-000-55).	715.00
8000-417B	Truss mount kit, black (K&M 24495-000-55).	415.00
8000-419B	Adapter for 36 mm tube, black (K&M 24521-300-55).	175.00
8000-418B	Security wire (K&M 24521-901-55)	150.00
8000-425B	Fixed telescopic table stand (K&M 23360-300-55).	200.00
8000-430	Carrying strap for one monitor.	100.00
8000-435B	Ceiling mount short, black (K&M 24485-000-55).	270.00
8000-435W	Ceiling mount short, white (K&M 24485-000-57).	270.00

NZ Dollar prices shown are ex-Wellington or Auckland warehouse, exclusive of GST.

All prices are subject to Protel Standard Conditions of Sale and subject to change without notice.

GENELEC PRICE LIST

08 January 2010

Price NZD excl. GST

Options for Two-Way Bi-Amplified Active Monitors

8000-440B	Cluster mount for 3 speakers, black	490.00
8000-440W	Cluster mount for 3 speakers, white	490.00
8020-490	Half 19" Rack mount kit for one 8020A (two units needed for full 19")	220.00
8020-421	Soft carrying bag for two monitors	225.00
8000-902B	Slotwall bracket for 8020A-8030A standplate (K&M 44102-029-55)	150.00

Options for 8030A and 8130A

8000-409B	Floor stand (K&M 26741-029-55).	335.00
8000-412B	Wall mount with T-plate, black (K&M 24179-000-55)	200.00
8000-412W	Wall mount with T-plate, white (K&M 24179-000-57)	200.00
8030-404-W	Wall mount, white (Omnimount 20.5 WA)	230.00
8000-402B	Wall bracket, black (K&M 24475-000-55)	290.00
8000-402W	Wall bracket, white (K&M 24475-000-57).	290.00
8000-410B	Wall mount bracket, black	30.00
8000-410W	Wall mount bracket, white	30.00
8000-406	Table stand (K&M 23310-370-55).	205.00
8030-408	Stand plate for 8030A/ 8130A Iso-Pod (K&M 19623-329-55)	145.00
8000-415B	Ceiling mount, black (K&M 24490-000-55).	715.00
8000-417B	Truss mount kit, black (K&M 24495-000-55).	495.00
8000-419B	Adapter for 36 mm tube, black (K&M 24521-300-55).	175.00
8000-418B	Security wire (K&M 24521-901-55)	110.00
8000-425B	Fixed telescopic table stand (K&M 23360-300-55).	200.00
8000-430	Carrying strap for one monitor	40.00
8000-435B	Ceiling mount short, black (K&M 24485-000-55).	270.00
8000-435W	Ceiling mount short, white (K&M 24485-000-57).	270.00
8000-440B	Cluster mount for 3 speakers, black	490.00
8000-440W	Cluster mount for 3 speakers, white	490.00
8030-421	Soft carrying bag for two monitors	230.00
8000-902B	Slotwall bracket for 8020A-8030A standplate (K&M 44102-029-55).	150.00

Options for 8040A and 8240A

8000-400	Floor stand "Genelec design" 1100/1700 mm high (K&M 26785-000-56)	690.00
8000-409B	Floor stand (K&M 26741-029-55)	335.00
8000-401B	Wall mount, black (K&M 24180-000-55)	175.00
8000-401W	Wall mount, white (K&M 24180-000-57)	175.00
8000-402B	Wall bracket, black (K&M 24475-000-55)	290.00
8000-402W	Wall bracket, white (K&M 24475-000-57)	290.00
8000-406	Table stand (K&M 23310-370-55).	205.00
8040-408	Stand plate for 8040A Iso-Pod (K&M 19624-329-55)	155.00
8000-415B	Ceiling mount, black (K&M 24490-000-55).	715.00
8000-417B	Truss mount kit, black (K&M 24495-000-55).	495.00
8000-419B	Adapter for 36 mm tube, black (K&M 24521-300-55).	175.00
8000-418B	Security wire (K&M 24521-901-55)	110.00

NZ Dollar prices shown are ex-Wellington or Auckland warehouse, exclusive of GST.

All prices are subject to Protel Standard Conditions of Sale and subject to change without notice.

GENELEC PRICE LIST

08 January 2010

Price NZD excl. GST

Options for Two-Way Bi-Amplified Active Monitors

8000-430	Carrying strap for one monitor.	40.00
8000-435B	Ceiling mount short, black (K&M 24485-000-55).	270.00
8000-435W	Ceiling mount short, white (K&M 24485-000-57).	270.00
8040-421	Soft carrying bag for two monitors	255.00
8040-450B	Flush mount kit	745.00
8000-904B	Slotwall bracket for 8040A-8050A standplate (K&M 44104-029-55).	155.00

Options for 8050A and 8250A

8000-400	Floor stand "Genelec design" 1100/1700 mm high (K&M 26785-000-56)	690.00
8000-409B	Floor stand (K&M 26741-029-55)	335.00
8000-402B	Wall bracket, black (K&M 24475-000-55)	290.00
8000-402W	Wall bracket, white (K&M 24475-000-57).	290.00
8050-405-B	Ceiling mount, black (Omnimount 60.0 CA)	340.00
8050-408	Stand plate for 8050A Iso-Pod (K&M 19625-329-55)	165.00
8000-415B	Ceiling mount, black (K&M 24490-000-55).	715.00
8000-417B	Truss mount kit, black (K&M 24495-000-55).	495.00
8000-419B	Adapter for 36 mm tube, black (K&M 24521-300-55).	175.00
8000-418B	Security wire (K&M 24521-901-55).	110.00
8000-430	Carrying strap for one monitor.	40.00
8000-435B	Ceiling mount short, black (K&M 24485-000-55).	270.00
8000-435W	Ceiling mount short, white (K&M 24485-000-57).	270.00
8050-421	Soft carrying bag for one monitor	245.00
8050-450B	Flush mount kit	805.00
8000-904B	Slotwall bracket for 8040A-8050A standplate (K&M 44104-029-55).	155.00

Options for 1032A

1032-450B	Stand plate with 3/8" thread, tiltable 15° black (K&M 24455-000-55) needs a stand, 8000-409B	335.00
8000-409B	Floor stand with 3/8" thread in top. (K&M 26741-029-55)	335.00
1032-460B	Wall mount black, tiltable 15° (K&M 24453-000-55)	735.00
1032-403	Magnetic shield upgrade kit	225.00
1032-409	Grille, black	210.00
1037-412	Rack Mount Adapter for amplifier unit (without cables)	435.00
1039-203	Cable 2 m	435.00
1039-204	Cable 5 m	525.00
1039-205	Cable 10 m	745.00
1039-206	Cable 15 m	920.00
1039-207	Cable 20 m	1,105.00

Options for Three-Way Tri-Amplified Active Monitors

Options for 8260A

8260-415B	Floor stand "Genelec design" 800/1350 mm high, 19kg (K&M 26795-000-56)	1,030.00
8260-414B	Wall bracket, black (K&M 24478-000-55)	345.00

NZ Dollar prices shown are ex-Wellington or Auckland warehouse, exclusive of GST.

All prices are subject to Protel Standard Conditions of Sale and subject to change without notice.

GENELEC PRICE LIST

08 January 2010

Price NZD excl. GST

Options for Three-Way Tri-Amplified Active Monitors

8260-450B	Stand plate for 8260A Iso-Pod (K&M 19628-300-56)	290.00
-----------	--	--------

Options for 1037C

1001-406	Handles (set of two, factory installed)	355.00
1037-409	Grille, black	245.00
1037-412	Rack Mount Adapter for amplifier unit (without cables)	375.00
1039-203	Cable 2 m	375.00
1039-204	Cable 5 m	525.00
1039-205	Cable 10 m	705.00
1039-206	Cable 15 m	900.00
1039-207	Cable 20 m	1,085.00

Options for 1038B and 1038BC

1001-406	Handles for 1038A/B (set of two, factory installed)	355.00
1038-409	Grille for 1038B, black	265.00
1038-409BC	Grille for 1038BC, black	265.00
1038-421	Rack Mount Adapter for 1038B amp without cables. (1038BC do not need rack mount adapter)	545.00
1039-203	Cable 2 m	375.00
1039-204	Cable 5 m	525.00
1039-205	Cable 10 m	705.00
1039-206	Cable 15 m	900.00
1039-207	Cable 20 m	1,085.00

Options for Main Control Room Active Monitors

Options for 1034B and 1034BCM

1034-403B	Magnetic shielding for 1034B (1034BCM is always shielded)	620.00
1034-409B	Grille for 1034B, black	275.00
1034-409BC	Grille for 1034BC, black	275.00
1039-203	Cable 2 m	375.00
1039-204	Cable 5 m	465.00
1039-205	Cable 10 m	805.00
1039-206	Cable 15 m	960.00
1039-207	Cable 20 m	1,125.00

Options for 1039A

1039-403	Magnetic shielding	620.00
1039-409	Grille, black	285.00
1039-203	Cable 2 m	375.00
1039-204	Cable 5 m	465.00
1039-205	Cable 10 m	805.00
1039-206	Cable 15 m	960.00
1039-207	Cable 20 m	1,125.00

Options for 1035B

NZ Dollar prices shown are ex-Wellington or Auckland warehouse, exclusive of GST.

All prices are subject to Protel Standard Conditions of Sale and subject to change without notice.

GENELEC PRICE LIST

08 January 2010

Price NZD excl. GST

Options for Main Control Room Active Monitors

1035-409	Grille, black	285.00
1035-204	Cable 5 m	1,090.00
1035-205	Cable 10 m	1,430.00
1035-206	Cable 15 m	1,620.00
1035-207	Cable 20 m	3,620.00
1035-208	Cable 25 m.	4,350.00
1035-209	Cable 30 m	5,220.00

Options for 1036A

1036-409	Grille, black	285.00
1035-204	Cable 5 m	1,090.00
1035-205	Cable 10 m	1,430.00
1035-206	Cable 15 m	1,620.00
1035-207	Cable 20 m	3,620.00
1035-208	Cable 25 m.	4,350.00
1035-209	Cable 30 m.	5,220.00

Options for Active Subwoofer Systems

Options for 7060B, 7070A, 7071A and 7260A, 7270A, 7271A and 7073A

1092-400	Remote Bypass switch box with 1/4" jack connector	155.00
7000-415	Remote Power/Overload LED box with 5 m cable, RJ11 connector	255.00
7000-416	Remote control box for Bypass and LFE +10 dB functions with 5 m cable, RJ11 connector	255.00

Cable

Options for 7060B, 7070A, 7071A and 7260A, 7270A, 7271A and 7073A

1510-302B	Hybrid cable black (Power and AES/EBU) 50 m reels	815.00
1550-105	Loom 5 meter, with DB 25 pin male and 8 pcs XLR female connectors <small>Providing AD9200A connectivity to 8 pcs XLR balanced monitor outputs.(TAN08DF05)</small>	720.00